

Tornio Pentamac QT 1500 / Lathe Pentamac QT 1500


- Make Pentamac
- Tip height 230 mm
- Turnable diameter on the slide 250 mm
- Turning diameter in the recess 700 mm
- Width of the recess 280 mm
- Distance between centers 1500 mm
- Width between guides (center - center of carriage support) 270 mm
- Chute width 240 mm
- Spindle
- Manual self-centering spindle diameter 250 mm
- Hydraulic self-centering spindle diameter 250 mm
- Bar passage (spindle photo) 78 mm
- Bar passage with hydraulic chuck 65 mm
- A.C. motor power 7.5 Kw
- Spindle speed 40 - 2000 RPM varia. electronic Inverter
- Tailstock
- Maximum quill stroke 135 mm
- Quill diameter 55 mm
- M5 taper
- VIESEL VSC1020 T CNC
- TFT 8.4" full color display, Memory 1Gb, graphic editor, compilation for graphic cycles, for self-learning, ISO language, LAN network socket, USB key
- Electronic handwheels on sliding leaf (distinct X-Z axes) with x1-x10 resolution selector
- Rapid joystick on sliding leaf

SIDICOM

Sede Amm/Comm.:

Via Bachelet, 20

35010 LIMENA (PD) -ITALY

Sede Amm/Comm.:

Via Bachelet, 20

35010 LIMENA (PD) -ITALY

Tel. +39 049 769998 - Fax. +39 049 767778

www.sidicom.it - email: commerciale@sidicom.it

- YANTAY electric turret: 6-position vertical (change 1.4 sec)
- Tool shank size 25 x 25 mm
- Cylindrical shank holder size: dia 25 mm (for tapered sockets up to M 1-2)
- Dimensions 2800 x 1200 x 1600 h mm
- Net weight 2900 kg (structure entirely of cast iron)

